

FLEXI BUTTON

Heavy duty deep stud floor covering

A multi-purpose, heavy duty sheet vinyl for commercial and medium duty industrial applications.

The distinctive deep stud design is not only an attractive feature but a practical one. Flexi Button is easy to clean, slip resistant, chemical, oil and acid resistant and formulated to cope with light spillages.



BENEFITS

- Good slip resistance and hardwearing
- Chemical, oil and acid resistant
- Easy to cut on site, contours to uneven surfaces
- Quick to install
- Fire resistant

FEATURES

- Deep stud design
- Vinyl sheets in roll format
- Made from flexible PVC
- Supplied in convenient roll formats
- EN 13501 - I : 2007- Bfl - S1

STANDARD COLORS



BLUE



DARK GRAY



BLACK

STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTION
Flexi Button	1/8" (3.3mm)	3'2" x 65'7" (0.98 x 20m)



PRODUCT DATA SHEET: FLEXI BUTTON

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (in)	Length (ft)	Widths (ft)	Weight (lbs/sq.ft)
<i>Tolerances</i>	<i>+/- 0.05"</i>	<i>0+1.0'</i>	<i>+/- 1/2"</i>	
Flexi Button	1/8"	65'7"	3'2"	0.88



Flexi Button

GENERAL

- APPEARANCES Heavy duty deep stud pattern on a continuous sheet format.
- COLOURS Black, Dark Grey, Blue
- DURABILITY Continuous extruded sheet with high scuff resistance.
- WORKABILITY Available in rolls for ease of installation. Easy to cut to size and shape.
- USES Indoor or outdoor use for floor protection and floor enhancement.

TECHNICAL DATA

- CHEMICAL Resistant to most acids, alkalines and oils. For specific chemical resistances, www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf
- COMPOSITION Flexible DINP plasticized Polyvinyl Chloride (PVC).
- FIRE EN ISO 13501 - I : 2007 - Bfl - S1
- REVERSION Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf
- THERMAL Functional -9^oF +140^oF (slight size variation may occur at temperature extremes).
- UV LIGHT Resistance to PVC degradation.
- WARRANTY 2 years. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf

