

FLEXI COIN

The large stud vinyl alternative

Attractive large stud vinyl floor covering also available in 'eco' version.

Large areas can be covered economically using just one piece of material in 3'2" (98cm) or 5' (150cm) widths. This multi-purpose product is a high quality alternative to conventional floorings in many light duty applications.



BENEFITS

- Good slip resistance
- Chemical, oil and acid resistant
- Easy to cut on site, contours to uneven surfaces
- Quick to install
- Environmentally-friendly
- Fire resistant

FEATURES

- Large stud design
- Vinyl sheets in roll format
- Made from flexible PVC
- Supplied in convenient roll formats
- 'Eco' version manufactured from reprocessed recycled material
- EN 13501 - 1 : 2007- Bfl - S1

Eco Coin

The eco-friendly and economical version of Flexi Coin manufactured from 100% recycled material.


STANDARD COLORS

FLEXI COIN




BLUE

ECO COIN



DARK GRAY



BLACK


STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTIONS	
Flexi Coin	1/16" (1.6mm)	3'2" x 82' (0.98 x 25m)	5' x 82' (1.5 x 25m)
Eco Coin	1/16" (1.6mm)	3'2" x 82' (0.98 x 25m)	5' x 82' (1.5 x 25m)

PRODUCT DATA SHEET: FLEXI/ECO COIN

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (in)	Length (ft)	Widths (ft)		Weight (lbs/sq.ft)
<i>Tolerances</i>	+/- 0.05"	0+1.0'	+/- 1/2"		
Flexi Coin	1/16"	82'	3'2"	5'	0.49



GENERAL

- APPEARANCES Large stud pattern on a continuous sheet format.
- COLORS **Flexi Coin:** Blue **Eco Coin:** Dark Gray, Black
- DURABILITY Continuous extruded sheet with high scuff resistance.
- WORKABILITY Available in rolls for ease of installation. Easy to cut to size and shape.
- USES Indoor or outdoor use for floor protection and floor enhancement.

TECHNICAL DATA

- CHEMICAL Resistant to most acids, alkalines and oils. For specific chemical resistances, www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf
- COMPOSITION Flexible DINP plasticised Polyvinyl Chloride (PVC).
- FIRE EN ISO 13501 - I : 2007 - Bfl - S1
- REVERSION Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf
- THERMAL Functional -9°F +140°F (slight size variation may occur at temperature extremes).
- UV LIGHT Resistance to PVC degradation.
- WARRANTY 1 year. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf

