

Contemporary small dot pattern

A light duty, attractive vinyl in a choice of colours with a dot pattern as a main feature.

More than just attractive, but also highly functional, Flexi Dot performs well and the roll format enables large area coverage with a minimum of seams/joints.



BENEFITS

- Good slip resistance
- Chemical, oil and acid resistant
- Easy to cut on site, contours to uneven surfaces
- Quick to install
- Environmentally-friendly
- Fire resistant

FEATURES

- Dot pattern surface
- Vinyl sheets in roll format
- Made from flexible PVC
- Supplied in convenient roll formats
- 'Eco' version manufactured from reprocessed factory waste
- EN 13501 - 1 : 2007- Bfl - S1

Eco Dot

Providing an eco-friendly and economical alternative, Eco Dot is manufactured to the same specification but using recycled factory materials only.

Flexi Dot Extra & Eco Dot Extra

Thicker 2.5mm (3/32") versions for heavier traffic areas.

STANDARD COLOURS

FLEXI DOT



RED BLUE

ECO DOT



DARK GREY BLACK

FLEXI DOT EXTRA



RED BLUE

ECO DOT EXTRA



DARK GREY BLACK

STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTION
Flexi Dot	1.6mm (1/16")	25 x 0.98m (82' x 3'2")
Eco Dot	1.6mm (1/16")	25 x 0.98m (82' x 3'2")


PRODUCT	HEIGHT	STANDARD ROLL OPTION
Flexi Dot Extra	2.5mm (3/32")	20 x 0.98m (65' 7" x 3'2")
Eco Dot Extra	2.5mm (3/32")	20 x 0.98m (65' 7" x 3'2")

PRODUCT DATA SHEET: Flexi/Eco Dot Extra

Apr-17

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (mm)	Lengths (m)	Widths (cm)	Weight (kg/m ²)
<i>Tolerances (mm)</i>	<i>+/- 0.5</i>	<i>0+0.3</i>	<i>+/- 1</i>	
Flexi Dot/Eco Dot	1.6	25	98	2.35
Flexi Dot Extra/Eco Dot Extra	2.5	20	98	3.75



Flexi Dot &



Eco Dot & Extra

GENERAL

APPEARANCES	Contemporary small dot pattern on a continuous sheet format.	
COLOURS	Flexi Dot/Flexi Dot Extra: Red, Blue	Eco Dot/Eco Dot Extra: Dark Grey, Black
DURABILITY	Continuous extruded sheet with high scuff resistance.	
WORKABILITY	Available in rolls for ease of installation. Easy to cut to size and shape.	
USES	Indoor or outdoor use for floor protection and floor enhancement.	

TECHNICAL DATA

CHEMICAL	Resistant to most acids, alkalines and oils. For specific chemical resistances, www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf
COMPOSITION	Flexible DINP plasticised Polyvinyl Chloride (PVC).
FIRE	EN ISO 13501 - I : 2007 - Bfl - S1
REVERSION	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf
THERMAL	Functional -23°C +60°C (slight size variation may occur at temperature extremes).
UV LIGHT	Resistant to PVC degradation; uncoloured PVC material - BS EN 607 = Delta E 1.02.
WARRANTY	Flexi/Eco Dot: 1 year. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf Flexi Dot/Eco Dot Extra: 2 years