

## Fine ribbed matting

**Fluted surface resists oils, chemicals and acids.**

The practical alternative to conventional rubber runners, Flexi Line is a fine ribbed vinyl matting designed for areas alongside or on top of benches. Flexi Line has a slip resistant fluted surface and dense composition to reduce the impact of noise and/or vibration.



### BENEFITS

- Good slip resistance
- Chemical, oil and acid resistant
- Easy to cut on site, contours to uneven surfaces
- Quick to install
- Fire resistant

### FEATURES

- Fine ribbed surface
- Vinyl sheets in roll format
- Made from flexible PVC
- Supplied in convenient roll formats
- EN 13501 - I : 2007- Bfl - S1


### STANDARD COLORS



RED



LIGHT GRAY



BLACK

### STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTION
Flexi Line	5/64" (2mm)	3'3" x 82' (1 x 25m)



# PRODUCT DATA SHEET: FLEXI LINE

## SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (in)	Length (ft)	Widths (ft)	Weight (lbs/sq.ft)
<i>Tolerances</i>	<i>+/- 0.05"</i>	<i>0+1.0'</i>	<i>+/- 1/2"</i>	
Flexi Line	5/64"	82'	3'3"	0.45



Flexi Line

## GENERAL

- APPEARANCES** Fine ribbed pattern on a continuous sheet format.
- COLORS** Black, Light Gray, Red
- DURABILITY** Continuous extruded sheet with high scuff resistance.
- WORKABILITY** Available in rolls for ease of installation. Easy to cut to size and shape.
- USES** Indoor or outdoor use for floor protection and floor enhancement.

## TECHNICAL DATA

- CHEMICAL** Resistant to most acids, alkalines and oils. For specific chemical resistances, [www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf](http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf)
- COMPOSITION** Flexible DINP plasticized Polyvinyl Chloride (PVC).
- FIRE** EN ISO 13501 - I : 2007 - Bfl - S1
- REVERSION** Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to [www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf](http://www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf)
- THERMAL** Functional -9°F +140°F (slight size variation may occur at temperature extremes).
- UV LIGHT** Resistance to PVC degradation.
- WARRANTY** 1 year. See [www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf](http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf)

