

Fine ribbed matting

Fluted surface resists oils, chemicals and acids.

The practical alternative to conventional rubber runners, Flexi Line is a fine ribbed vinyl matting designed for areas alongside or on top of benches. Flexi Line has a slip resistant fluted surface and dense composition to reduce the impact of noise and/or vibration.




BENEFITS

- Good slip resistance
- Chemical, oil and acid resistant
- Easy to cut on site, contours to uneven surfaces
- Quick to install
- Fire resistant

FEATURES

- Fine ribbed surface
- Vinyl sheets in roll format
- Made from flexible PVC
- Supplied in convenient roll formats
- EN 13501 - 1 : 2007- Bfl - S1


STANDARD COLOURS



RED



LIGHT GREY



BLACK

STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTION
Flexi Line	2mm (5/64")	25 x 1m (82' x 3'3")



PRODUCT DATA SHEET: Flexi Line

Apr-17

SIZES & WEIGHTS

<i>All dimensions are nominal</i>					
	Height (mm)	Lengths (m)	Widths (cm)	Weight (kg/m ²)	
	<i>Tolerances (mm)</i>	<i>+/- 0.5</i>	<i>0+0.3</i>	<i>+/- 1</i>	
Flexi Line	2	25	100	2.2	



Flexi Line

GENERAL

- APPEARANCES** Fine ribbed pattern on a continuous sheet format.
- COLOURS** Black, Light Grey, Red
- DURABILITY** Continuous extruded sheet with high scuff resistance.
- WORKABILITY** Available in rolls for ease of installation. Easy to cut to size and shape.
- USES** Indoor or outdoor use for floor protection and floor enhancement.

TECHNICAL DATA

- CHEMICAL** Resistant to most acids, alkalines and oils. For specific chemical resistances, www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf
- COMPOSITION** Flexible DINP plasticised Polyvinyl Chloride (PVC).
- FIRE** EN ISO 13501 - I : 2007 - Bfl - S1
- REVERSION** Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf
- THERMAL** Functional -23⁰C +60⁰C (slight size variation may occur at temperature extremes).
- UV LIGHT** Resistant to PVC degradation; uncoloured PVC material - BS EN 607 = Delta E 1.02.
- WARRANTY** 1 year. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf



Plastic Extruders Ltd, Russell Gardens, Wickford, SS11 8DN, UK
Tel: +44(0)1268 571116

Web: www.plastexmatting.com