

FLEXI RIDGE

Hard wearing ribbed matting

For component protection and dispersion of light spillages.

Scuff resistant flooring or bench top matting with high component and noise protection featuring easy to clean ridges to enhance resilience and disperse light spillages, in a one piece continuous roll.



BENEFITS

- Good slip and wear resistance
- Chemical, oil and acid resistant
- Easy to cut on site, contours to uneven surfaces
- Quick to install
- Fire resistant

FEATURES

- Ribbed surface
- Vinyl sheets in roll format
- Made from flexible PVC
- Supplied in convenient roll formats
- EN 13501 - I : 2007- Bfl - S1

STANDARD COLORS



GREEN



DARK GRAY



STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTION
Flexi Ridge	7/16" (2.8mm)	3'3" x 65'7" (1 x 20m)

PRODUCT DATA SHEET: FLEXI RIDGE

Jun-18

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (in)	Length (ft)	Widths (ft)	Weight (lbs/sq.ft)
<i>Tolerances</i>	<i>+/- 0.05"</i>	<i>0+1.0'</i>	<i>+/- 1/2"</i>	
Flexi Ridge	7/16"	65'7"	3'3"	0.50



Flexi Ridge

GENERAL

APPEARANCES	Hard wearing ribbed pattern on a continuous sheet format.
COLORS	Green, Dark Gray
DURABILITY	Continuous extruded sheet with high scuff resistance.
WORKABILITY	Available in rolls for ease of installation. Easy to cut to size and shape.
USES	Indoor or outdoor use for floor protection and floor enhancement.

TECHNICAL DATA

CHEMICAL	Resistant to most acids, alkalines and oils. For specific chemical resistances, www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf
COMPOSITION	Flexible DINP plasticized Polyvinyl Chloride (PVC).
FIRE	EN ISO 13501 - I : 2007 - Bfl - S1
REVERSION	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf
THERMAL	Functional -9°F +140°F (slight size variation may occur at temperature extremes).
UV LIGHT	Resistance to PVC degradation.
WARRANTY	1 year. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf



Plastex Matting Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.
Sales Tel: 256.845.7725

Web: www.plastexmatting.com