

# FLOORLINE WATER POLO

## The field marking matting

An efficient dual purpose field marking system easily applied and removed to increase visibility of the field lines while ensuring safe pool side traffic thanks to its slip resistant properties.

Floorline Water Polo matting is very convenient to use at public polo sessions, being light, quick and easy to install and for subsequent storage.

Floorline Water Polo matting is supplied as a one piece tri-coloured 15m roll (green, yellow and red), acting as a field marking solution whilst ensuring continued safety underfoot for the referee even when the matting is wet.




### BENEFITS

- Certified slip resistance  
DIN 51130: R11 DIN 51097: C ASTM 1677: I.0/0.8
- Excellent drainage DIN 51130: V10
- Excellent hygiene
- Quick to lay down for field set-up
- Increase visibility of field marking lines
- Easy to store and carry
- UV resistant
- Fire resistant


### FEATURES

- Etched surface
- Open grid construction
- Anti-microbial & anti-fungal additives
- Made from flexible PVC, supplied in one piece roll
- Tri-coloured one piece roll:  
Green (10m), yellow (3m) and red (2m)
- 38cm diameter when rolled
- Can be used indoor or outdoor\*
- Certified EN 13501: Cf1 - S1


### STANDARD COLOURS



RED\*



YELLOW



GREEN

Floorline Water Polo is a Tri-Coloured mat, making up the three colours of red, yellow and green.

\* Red colour is not colourfast in continual direct sunlight.

### STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTIONS**	
Floorline Water Polo	6mm (1/4")	15 x 0.6m (49' x 2')	15 x 0.91m (49' x 3')

\*\*Contact us for bespoke dimensions.



**Plastic Extruders Ltd**, Russell Gardens, Wickford, SS11 8DN, UK  
Tel: +44(0)1268 571116


Web: [www.plastexmatting.com](http://www.plastexmatting.com)

# PRODUCT DATA SHEET: FLOORLINE WATER POLO

Jun-18

## SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (mm)	Length (m)	Widths (cm)		Weight (kg/m <sup>2</sup> )
<i>Tolerances</i>	<i>+/-0.5</i>	<i>0+0.3</i>	<i>+/- 1</i>		
Floorline Water Polo	6	15	60	91	3.7



## GENERAL

APPEARANCES	Open grid “duckboard” design with hollow cushioned surface.
COLOURS	Available as a tri-coloured 15m roll in Red (2m), Yellow (3m) and Green (10m). Red colour is not colourfast in direct sunlight.
DURABILITY	One piece welded construction for maintenance free life.
WORKABILITY	Flexible construction is easy to cut and shape on site. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.
USES	Water polo field marking system.

## TECHNICAL DATA

ACOUSTIC	Excellent sound absorption properties.
CHEMICAL	Resistant to most acids, alkalines and oils. For specific chemical resistances, see <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf">www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf</a>
COMPOSITION	Flexible DINP plasticised Polyvinyl Chloride (PVC).
ENVIRONMENT	Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products. All products are 100% recyclable. * Registration, Evaluation, Authorisation and Restriction of Chemical substances
FIRE	DIN 4102 Part I - Classification B2. BS 2782 Part I, method 140A: 1992 (ISO 1210: 1992)
HYGIENE	Non-porous 100% Virgin PVC - Inhibits the growth of bacteria. BPR (EU Biocidal Products Regulation 528/2012): Contains Biocidal Products for improved performance. Use Floorline safely. Always read the label and product information before use.
Anti-bacterial	SteriTouch additive; Test JIS Z 2801:2000 – Determination of the antibacterial effect against: Staphylococcus aureus E. Coli Result - Antimicrobial pass of >99.99% Result - Antimicrobial pass of >99.99%
Anti-fungal	SteriTouch additive; Test method ASTM G21-09 - Determining resistance to fungi. Result - Nil Growth after 2 weeks
SLIP RESISTANCE	ASTM F 1677 - Dry/Wet: 1.0/0.8 DIN51097: Classification C
REVERSION	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf">www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf</a>
THERMAL	Functional -23°C +60°C (slight size variation may occur at temperature extremes).
UV LIGHT	Resistance to PVC degradation.
WARRANTY	1 year. See <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf">www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf</a>



Plastic Extruders Ltd, Russell Gardens, Wickford, SS11 8DN, UK  
Tel: +44(0)1268 571116

Web: [www.plastexmatting.com](http://www.plastexmatting.com)