

FRONTRUNNER BRUSH WIDE

Extra wide grid matting with brush inserts

For large debris removal in external areas.

Icy/snowy winter months can be characterized by a lot of gravel, snow or stones.

With similar properties to Frontrunner Brush, but with a wider grid that allows larger debris such as small stones to fall through and be contained.

It works either as a stand alone or can be interchanged with another Frontrunner system in summer months to provide the complete entrance solution.




BENEFITS

- Ideal for removing salt, snow or gravel
- High soil removal and slip resistance
- Excellent drainage
- Excellent scraping
- Fire resistant
- Easy to maintain
- Seamless, quick and easy installations
- Easy to cut on site, contours to uneven surfaces

FEATURES

- Extra wide grid
- Diamond cut pattern
- Two layer open grid construction
- Nylon brush inserts
- EN 13501 - 1 : 2007- Cf1 - S1
- Can be rolled up or lifted for cleaning
- Supplied in 33' (10m) rolls - modules also available
- Made from flexible PVC

STANDARD COLORS



DARK GRAY



BLACK



STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTIONS*			STANDARD MODULE OPTIONS**		
Frontrunner Brush Wide	9/16" - 3/4" (14-19mm)	2' x 33' (0.6 x 10m)	3' x 33' (0.91 x 10m)	4' x 16'6" (1.2 x 5m)	2' 7" x 4' (0.8 x 1.2m)	3' 3" x 4'11" (1 x 1.5m)	3' 7" x 6'7" (1.1 x 2m)

*Contact us for custom dimensions.

**Surface modules are supplied with factory fitted PVC ramped edging to four sides.




Plastex Mattinc Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.
Sales Tel: 256.845.7725

Web: www.plastexmatting.com

PRODUCT DATA SHEET: Frontrunner Brush Wide

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (in)	Length (ft)	Widths (ft)		Weight (lbs/sq.ft)
<i>Tolerances</i>	<i>+/- 0.05"</i>	<i>0+1.0'</i>	<i>+/- 1/2"</i>		
Frontrunner Brush Wide	9/16" - 3/4"	33'	2'	3'	1.6
Frontrunner Brush Wide	9/16" - 3/4"	16'6"		4'	1.6



GENERAL

APPEARANCES Wide spaced open grid design with nylon brush inserts.

COLORS Black and Dark Gray homogenous stable colors.

DURABILITY All welded durable construction for long effective usage.

INSTALLATION **Recessed wells:**
www.plastexmatting.com/uploads/4/4/0/0/44003899/frontrunner-installation-guide-recessed-applications.pdf
Surface mounted applications:
www.plastexmatting.com/uploads/4/4/0/0/44003899/frontrunner-installation-guide-surface-mounted-applications.pdf

WORKABILITY Flexible construction is easy to cut and shape on site.
 Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.

USES Large debris removal in external areas. For Retail, Hospitality, Offices, Restaurants, Leisure, Industrial, Education, High commercial applications, etc.

TECHNICAL DATA

ACOUSTIC Excellent sound absorption properties.

CHEMICAL Resistant to most acids, alkalines and oils (for specific chemical resistances, see www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf)

COMPOSITION Flexible Polyvinyl Chloride (PVC)

Nylon Brush Inserts: see below

<i>Construction</i>	Aligned Tufting	<i>Bristle diameter</i>	0.012 in	<i>Insert thickness</i>	0.47 in
<i>Bristle content</i>	Nylon 6.6 Monofilaments	<i>Bristle height</i>	3/16 in	<i>Backing</i>	PVC

ENVIRONMENT It has been determined under the guidelines for the State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), that no warning labels or information provision are required for Frontrunner Brush Wide.

Our Frontrunner Entrance matting System qualifies for LEED IEQ Credit 5.

When produced in Black or Gray, our Frontrunner range may also qualify for LEED MR Credit 4.

Our Black PVC matting is manufactured with our post-industrial recycled material. The recycled content averages at least 30%, but we strive for 100% where possible.

Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products.

* Registration, Evaluation, Authorization and Restriction of Chemical substances

FIRE **Nylon Brush fibres:** UL94 - V2

REVERSION Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf

THERMAL Functional -9°F +140°F (slight size variation may occur at temperature extremes).

UV LIGHT Resistant to PVC degradation.

WARRANTY 2 years. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf



Plastex Matting Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.
 Sales Tel: 256.845.7725

PRODUCT DATA SHEET: Frontrunner Brush Wide

ANCILLARIES



2 1/2" PVC edging strip
Supplied in rolls of 33' (10.1m) length
with cold welding paste.
9/16" x 2 1/2" x 33'
(14mm x 60mm x 10.1m) **Colors:** Black and Dark Gray



1 13/16" Aluminum edging strip
Supplied in sections of 6'6" (2m) length
with fixing screws and plugs.
5/8" x 1 13/16" x 6'6"
(15mm x 45mm x 2m) **Color:** Anodized Aluminum



3 3/4" PVC edging strip
Supplied in rolls of 33' (10.1m) length
with cold welding paste.
9/16" x 3 3/4" x 33'
(14mm x 100mm x 10.1m) **Colors:** Black and Dark Gray



Snap Track
2 part snap track can be welded to join
rolls end to end or side to side for large area
covering. Supplied with cold welding paste.
9/16" x 8'2"
(14mm x 2.5m) **Color:** Dark Gray

