

FRONTRUNNER BRUSH WIDE

Extra wide grid matting with brush inserts

For large debris removal in external areas.

Icy/snowy winter months can be characterised by a lot of gravel, shingle or stones.

With similar properties to Frontrunner Brush, but with a wider grid that allows larger debris such as small stones to fall through and be contained.

It works either as a stand alone or can be interchanged with another Frontrunner system in summer months to provide the complete entrance solution.



BENEFITS

Ideal for removing salt, shingle or gravel

High soil removal and slip resistance

Excellent drainage

Excellent scraping

Fire resistant

Easy to maintain

Seamless, quick and easy installations

Easy to cut on site, contours to uneven surfaces

FEATURES

Extra wide grid

Diamond cut pattern

Two layer open grid construction

Nylon brush inserts


EN 13501 - 1 : 2007- Cfl - S1

Can be rolled up or lifted for cleaning

Supplied in 10m (33') rolls - modules also available

Made from flexible PVC

STANDARD COLOURS



DARK GREY



BLACK



STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTIONS*			STANDARD MODULE OPTIONS**		
Frontrunner Brush Wide	14-19mm (9/16" - 3/4")	10 x 0.6m (33' x 2')	10 x 0.91m (33' x 3')	5 x 1.2m (16'6" x 4')	0.8 x 1.2m (2'7" x 4')	1 x 1.5m (3'3" x 4'11")	1.1 x 2m (3'7" x 6'7")

*Contact us for bespoke dimensions.


**Surface modules are supplied with factory fitted PVC ramped edging to four sides.

PRODUCT DATA SHEET: FRONTRUNNER BRUSH WIDE

Aug-18

SIZES & WEIGHTS

	<i>All dimensions are nominal</i>				
	Height (mm)	Length (m)	Widths (cm)		Weight (kg/m ²)
	<i>Tolerances (mm)</i>	<i>+/- 0.5</i>	<i>0+0.3</i>	<i>0+2</i>	
Frontrunner Brush Wide	14/19	10	60	91	7.8
Frontrunner Brush Wide	14/19	5		120	7.8



GENERAL

APPEARANCES	Wide spaced open grid design with nylon brush inserts.
COLOURS	Black and Dark Grey. Other colours available on request.
DURABILITY	One piece welded construction for maintenance free life.
INSTALLATION	Recessed wells: www.plastexmatting.com/uploads/4/4/0/0/44003899/frontrunner-installation-guide-recessed-applications.pdf Surface mounted applications: www.plastexmatting.com/uploads/4/4/0/0/44003899/frontrunner-installation-guide-surface-mounted-applications.pdf
WORKABILITY	Flexible construction is easy to trim and shape on site. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.
USES	Large debris removal in external areas. For Retail, Hospitality, Offices, Restaurants, Leisure, Industrial, Education, High commercial applications, etc.

TECHNICAL DATA

ACOUSTIC	Excellent sound absorption properties.
CHEMICAL	Resistant to most acids, alkalines and oils. For specific chemical resistances, see www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf
COMPOSITION	Flexible DINP plasticised Polyvinyl Chloride (PVC).

Nylon Brush Inserts: see below

<i>Construction</i>	Aligned Tufting	<i>Bristle diameter</i>	0.012 in	<i>Insert thickness</i>	0.47 in
<i>Bristle content</i>	Nylon 6.6 Monofilaments	<i>Bristle height</i>	3/16 in	<i>Backing</i>	PVC

ENVIRONMENT	Our Black PVC matting is manufactured with our post-industrial recycled material. The recycled content averages at least 30%, but we strive for 100% where possible. Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products. * Registration, Evaluation, Authorisation and Restriction of Chemical substances
-------------	--

FIRE	Nylon Brush fibres: UL94 - V2
REVERSION	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf
THERMAL	Functional -23 ⁰ C +60 ⁰ C (slight size variation may occur at temperature extremes).
UV LIGHT	Resistance to PVC degradation.
WARRANTY	2 years. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf



Plastic Extruders Ltd, Russell Gardens, Wickford, SS11 8DN, UK
Tel: +44(0)1268 571116

Web: www.plastexmatting.com

PRODUCT DATA SHEET: FRONTRUNNER BRUSH WIDE

ANCILLARIES



14mm x 60mm x 10.1m
(9/16" x 2 1/2" x 33')

60mm PVC edging strip

Supplied in rolls of 10.1m (33') length with cold welding paste.

Colours: Black, Dark Grey, Dark Brown, Holly Green, Oxford Blue, Yellow



14mm x 100mm x 10.1m
(9/16" x 3 3/4" x 33')

100mm PVC edging strip

Supplied in rolls of 10.1m (33') length with cold welding paste.

Colours: Black, Dark Grey, Yellow



15mm x 45mm x 2m
(5/8" x 1 13/16" x 6'6")

45mm Aluminium edging strip

Supplied in sections of 2m (6'6") length with fixing screws and plugs.

Colours: Anodised Aluminium, Powder Coated Yellow



14mm x 2.5m
(9/16" x 8'2")

Snap Track

2 part snap track can be welded to join rolls end to end or side to side for large area covering. Supplied with cold welding paste.

Colours: Black, Dark Grey