

FRONTRUNNER PLUS



Open grid entrance matting with absorbent inserts

Maximum removal of residual dirt and moisture in high traffic internal areas.

Protects your internal floorings and reduces cleaning costs.

Frontrunner Plus, available in two heights, is an open grid vinyl construction spike heel proof and wheel-chair friendly entry mat that effectively removes, retains and dries soil and moisture from underfoot thanks to its slip resistant surface and absorbent inserts. The positioning of the scraper bars on Frontrunner Entrance Flooring System can be varied to allow the incorporation of a logo panel. The system is of one-piece vinyl construction and is therefore both quiet underfoot and ideal for use in conjunction with under floor and upright loss prevention systems.



BENEFITS

- High soil removal & slip resistance
- Excellent drainage
- Maximum moisture removal
- Fire resistant
- Easy to maintain
- Seamless, quick and easy installations
- Easy to cut on site, contours to uneven surfaces
- Heel and wheel-proof
- Reduces the need of a deeper matwell
- Enhanced branding or styling

FEATURES

- Diamond cut pattern
- Two layer open grid construction
- Absorbent inserts
- Certified EN 13501 - 1 : 2007- Cfl - S2 ASTM E648 : Class I
- Can be rolled up or lifted for cleaning
- Supplied in 33' (10m) rolls - modules also available
- Made from flexible PVC
- Close mesh grid matting
- Available in a low profile 13/32" (10.5mm) option
- Up to 50 different color combinations available

STANDARD COLORS

For grid colors and carpet color combinations please see pages 52-53.

STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTIONS*			STANDARD MODULE OPTIONS**		
Frontrunner Plus	9/16" - 5/8" (14 - 16mm)	2' x 3' (0.6 x 10m)	3' x 33' (0.91 x 10m)	4' x 33' (1.2 x 10m)	2' 7" x 3' 11" (0.8 x 1.2m)	3' 3" x 4' 11" (1 x 1.5m)	3' 7" x 6' 7" (1.1 x 2m)
Low Profile	13/32" - 1/2" (10.5 - 12mm)	2' x 33' (0.6 x 10m)	3' x 33' (0.91 x 10m)	4' x 33' (1.2 x 10m)			

*Contact us for custom dimensions.

**Surface modules are supplied with factory fitted PVC ramped edging to four sides.

Frontrunner Plus Low Profile

A low profile 13/32" (10.5mm) option that aligns with standard ceramic floor tiles and carpets in recessed applications without the need to create a deeper matwell in an existing subfloor.




Plastex Mattinc Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.
Sales Tel: 256.845.7725

Web: www.plastexmatting.com

PRODUCT DATA SHEET: Frontrunner Plus

SIZES & WEIGHTS

<i>All dimensions are nominal Tolerances</i>	Height (in) <i>+/- 0.05"</i>	Length (ft) <i>0+1.0'</i>	Widths (ft) <i>+/- 1/2"</i>			Weight (lbs/sq.ft)
Frontrunner Plus	9/16"	33'	2'	3'	4'	2
Frontrunner Plus Low profile	13/32"	33'	2'	3'	4'	1.6



GENERAL

APPEARANCES

Open grid "heelproof" design with absorbent inserts.

COLORS

Black, Dark Gray, Brown, Lignite Brown, Holly Green and Oxford Blue homogenous stable colors. Other colors available on request.

Absorbent inserts: 4 color choices - 605, 606, 607 and 608. See www.plastexmatting.com/frontrunner-plus.html

DURABILITY

All welded durable construction for long effective usage.

INSTALLATION

Recessed wells:

www.plastexmatting.com/uploads/4/4/0/0/44003899/frontrunner-installation-guide-recessed-applications.pdf

Surface mounted applications:

www.plastexmatting.com/uploads/4/4/0/0/44003899/frontrunner-installation-guide-surface-mounted-applications.pdf

WORKABILITY

Flexible construction is easy to cut and shape on site.

Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.

USES

For maximum moisture removal in high traffic internal areas in Retail, Hospitality, Offices, Restaurants, Leisure, Industrial, Education, High commercial applications, etc.

TECHNICAL DATA

ACOUSTIC

Excellent sound absorption properties.

CHEMICAL

Resistant to most acids, alkalines and oils (for specific chemical resistances, see

www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf

COMPOSITION

Flexible Polyvinyl Chloride (PVC)

Absorbent Inserts: see below

<i>Zeno Protect Excellence</i>	605, 606, 607, 608
<i>Construction</i>	Tufted, Cut Pile
<i>Pile content</i>	100% nylon
<i>Pile weight</i>	0.22 lb/ft ² ± 5%
<i>Pile height</i>	± 1/4 in
<i>Total insert weight*</i>	0.9 lb/ft ² ± 5%

*Insert carpet & backing

<i>Zeno Protect Excellence</i>	605, 606, 607, 608
<i>Total insert height*</i>	± 3/8 in
<i>Primary Backing</i>	Non-Woven Polyester
<i>Secondary Backing</i>	Vinyl compound
<i>Flammability</i>	EN 13501-1 - Cfl-S1

*Insert carpet & backing



PRODUCT DATA SHEET: Frontrunner Plus

ENVIRONMENT

It has been determined under the guidelines for the State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), that no warning labels or information provision are required for Frontrunner Plus.

Our Frontrunner Entrance matting System qualifies for LEED IEQ Credit 5.

When produced in Black or Gray, our Frontrunner range may also qualify for LEED MR Credit 4.

Our Black PVC matting is manufactured with our post-industrial recycled material. The recycled content averages at least 30%, but we strive for 100% where possible.

Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products.

* Registration, Evaluation, Authorization and Restriction of CHemical substances

FIRE

Frontrunner Plus: EN ISO 13501-1:2007-Cfl-S2

ASTM E648 - Class I

Frontrunner Plus Low profile: EN ISO 13501-1:2007-Cfl-S2

Absorbent Inserts: see above

REVERSION

Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf

THERMAL

Functional -9°F +140°F (slight size variation may occur at temperature extremes).

UV LIGHT

Resistant to PVC degradation.

WARRANTY

Frontrunner Plus: 3 years. See

www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf

Frontrunner Plus Low Profile: 2 years

FRONTRUNNER PLUS ANCILLARIES



9/16" x 2 1/2" x 33'
(14mm x 60mm x 10.1m)

2 1/2" PVC edging strip

Supplied in rolls of 33' (10.1m) length with cold welding paste.

Colors: Black, Dark Gray



9/16" x 8'2"
(14mm x 2.5m)

Snap Track

2 part snap track can be welded to join rolls end to end or side to side for large area covering. Supplied with cold welding paste.

Colors: Black, Dark Gray



9/16" x 3 3/4" x 33'
(14mm x 100mm x 10.1m)

3 3/4" PVC edging strip

Supplied in rolls of 33' (10.1m) length with cold welding paste.

Colors: Black, Dark Gray



Connector clips - Side to side

For joining sections of matting together side to side.

Supplied in packs of 10.



5/8" x 1 13/16" x 6'6"
(15mm x 45mm x 2m)

1 13/16" Aluminum edging strip

Supplied in sections of 6'6" (2m) length with fixing screws and plugs.

Color: Anodized Aluminum

FRONTRUNNER PLUS LOW PROFILE ANCILLARIES



3/8" x 2" x 33'
(10mm x 50mm x 10.1m)

2" PVC edging strip

Supplied in rolls of 33' (10.1m) length with cold welding paste.

Colors: Black, Dark Gray



13/32" x 8'2"
(10.5mm x 2.5m)

Snap Track Low Profile

2 part snap track can be welded to join rolls end to end or side to side for large area covering. Supplied with welding paste.

Colors: Black, Dark Gray



Plastex Matting Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.

Sales Tel: 256.845.7725

Web: www.plastexmatting.com