

FRONTRUNNER SB

Vinyl ribbed, solid backed entrance matting

Laid directly on top of sub-floor, Frontrunner SB, being 1/4" thick, removes the need for a matwell and fits easily within existing floor coverings or surrounded by carpet tiles.

Frontrunner SB's ribbed pattern scrapes dirt at the entrance area, which is effectively contained away from the traffic area. The solid backing and ribbed construction enable quick and effective vacuuming.

Frontrunner SB can also be used on top of current flooring with ramped edging to provide a slip resistant walkway.



BENEFITS

Certified slip resistance DIN 51130: R11 ASTM C1028: 0.6/0.6

Fire resistant

Surface mounted

Can be adhered to sub-floor in high traffic areas

Easy to cut on site, contours to uneven surfaces

Seamless, quick and easy installations

Lightweight

Heel and wheel-proof

Rolling resistance

FEATURES

Etched pattern

Certified EN 13501 - 1 : 2007- Cfl - S1 ASTM E648: Class 2

1/4" (6.5mm) grid height

Solid backing

Made from flexible PVC

Supplied in 33' (10m)

One layer hollow construction

Close mesh grid matting

ASTM F2753: No apparent damage to the vinyl portion of the system after 1,000 cycles at 500lbs

STANDARD COLORS



BLACK



GRAY



STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTION
Frontrunner SB	1/4" (6.5mm)	3'3" x 33' (1 x 10m)



Plastex Mattinc Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.
Sales Tel: 256.845.7725

Web: www.plastexmatting.com

PRODUCT DATA SHEET: Frontrunner SB

ANCILLARIES



1/4" x 1" x 197'
(6.5mm x 30mm x 60m)

1" PVC edging strip

Supplied in rolls of 60m (197') length
with cold welding paste.

Colors: Black, Dark Gray



1/8" x 11'9"
(3.5mm x 3.6m)

T joining I part strip

I part strip can be welded to join rolls end to
end or side to side for large area covering.

Color: Black



Plastex Matting Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.
Sales Tel: 256.845.7725

Web: www.plastexmatting.com