

# FRONTRUNNER SB

## Vinyl ribbed, solid backed entrance matting

Laid directly on top of sub-floor, Frontrunner SB, being 6.5mm thick, removes the need for a matwell and fits easily within existing floor coverings or surrounded by carpet tiles.

Frontrunner SB's ribbed pattern scrapes dirt at the entrance area, which is effectively contained away from the traffic area. The solid backing and ribbed construction enable quick and effective vacuuming.

Frontrunner SB can also be used on top of current flooring with ramped edging to provide a slip resistant walkway.



### BENEFITS

- Certified slip resistance DIN 51130: R11 ASTM C1028: 0.6/0.6
- Fire resistant
- Surface mounted
- Can be adhered to sub-floor in high traffic areas
- Easy to cut on site, contours to uneven surfaces
- Seamless, quick and easy installations
- Light to handle
- Heel and wheel-proof
- Rolling resistance

### FEATURES

- Etched pattern
- Certified EN 13501 - I : 2007- Cf1 - S1 ASTM E648: Class 2
- 6.5mm (17/64") grid height
- Solid backing
- Made from flexible PVC
- Supplied in 10m (33') and 20m (66') rolls
- One layer hollow construction
- Close mesh grid matting
- ASTM F2753: No apparent damage to the vinyl portion of the system after 1,000 cycles at 500lbs

### STANDARD COLOURS



BLACK



GREY



### STANDARD SIZES


PRODUCT	HEIGHT	STANDARD ROLL OPTIONS	
Frontrunner SB	6.5mm (17/64")	10 x 1m (33' x 3'3")	20 x 1m (66' x 3'3")

# PRODUCT DATA SHEET: FRONTRUNNER SB

Aug-18

## SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (mm)	Length (m)	Width (cm)	Weight (kg/m <sup>2</sup> )
<i>Tolerances (mm)</i>	<i>+/- 0.5</i>	<i>0+0.3</i>	<i>0+2</i>	
Frontrunner SB	6.5	10	100	6.3




## GENERAL

APPEARANCES	Open ribbed "heelproof" design on vinyl sheet.
COLOURS	Black and Dark Grey homogenous stable colours. Other colours available on request.
DURABILITY	One piece welded construction for maintenance free life.
INSTALLATION	Loose laid or adhered to sub-floor: <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/frontrunner-sb-sb-plus-installation-instructions.pdf">www.plastexmatting.com/uploads/4/4/0/0/44003899/frontrunner-sb-sb-plus-installation-instructions.pdf</a>
WORKABILITY	Flexible construction is easy to trim and shape on site. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.
USES	For medium to high traffic internal areas in Retail, Hospitality, Offices, Restaurants, Leisure, Industrial, Education, High commercial applications, etc.


## TECHNICAL DATA

ACOUSTIC	Excellent sound absorption properties.
CHEMICAL	Resistant to most acids, alkalines and oils. For specific chemical resistances, see <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf">www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf</a>
COMPOSITION	Flexible DINP plasticised Polyvinyl Chloride (PVC).
ENVIRONMENT	Our Black PVC matting is manufactured with our post-industrial recycled material. The recycled content averages at least 30%, but we strive for 100% where possible. Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products. Frontrunner SB is 100% recyclable. * Registration, Evaluation, Authorisation and Restriction of Chemical substances
FIRE	EN ISO 13501-1:2007-Cfl-S1 ASTM E648 - Class 2
REVERSION	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf">www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf</a>
ROLLING RESISTANCE	ASTM F 2753: No apparent damage to the vinyl portion of the system after 1,000 cycles at 500lbs
SLIP RESISTANCE	DIN 51130: R11, V10 ASTM F C1028 - Dry/Wet: 0.6/0.6
THERMAL	Functional -23°C +60°C (slight size variation may occur at temperature extremes).
UV LIGHT	Resistance to PVC degradation.
WARRANTY	3 Years. See <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf">www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf</a>

## ANCILLARIES



**30mm PVC edging strip**  
Supplied in rolls of 60m (197') length with cold welding paste.  
**Colours:** Black, Dark Grey



**T joining I part strip**  
I part strip can be welded to join rolls end to end or side to side for large area covering.  
**Colour:** Black



**Plastic Extruders Ltd**, Russell Gardens, Wickford, SS11 8DN, UK  
Tel: +44(0)1268 571116

Web: [www.plastexmatting.com](http://www.plastexmatting.com)