

# HERONRIB

## Hygienic, comfortable, self draining barefoot matting

The ultimate sports and leisure matting for use in wet areas where barefoot traffic is extensive.

Made from strong, non-porous PVC with channelled underbars, Heronrib will automatically self drain even the largest amounts of water: It is therefore perfect to dissipate a splash while creating one around swimming pools, saunas, jacuzzis and other wet areas with the many available attractive Heronrib's colors.



### BENEFITS

Certified slip resistance DIN 51097: C ASTM 1677: 0.9/0.7

4 way drainage

Excellent hygiene

Easy to cut and clean, contours to uneven surfaces

Quick to install

UV resistant

Fire resistant

Enhanced branding or styling

### FEATURES

Embossed surface

Two layer construction and channelled underbars

Anti-microbial and anti-fungal additives

Made from flexible PVC

Supplied in 33' (10m) rolls

Can be used indoor or outdoor

Certified EN 13501: Cfl - S1

6 standard colors

### STANDARD COLORS



OXFORD BLUE



OCEAN BLUE



CHARCOAL GRAY



FOREST GREEN



BUFF



WHITE

Other colors available on request.

### STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTIONS*			
Heronrib	13/32" (10.5mm)	2' x 33' (0.6 x 10m)	3' x 33' (0.91 x 10m)	3'3" x 33' (1 x 10m)	4' x 33' (1.22 x 10m)

\*Contact us for custom dimensions.





**Plastex Mattinc Inc.**, 120 55th Street NE Fort Payne, AL 35967 U.S.A.  
Sales Tel: 256.845.7725

Web: [www.plastexmatting.com](http://www.plastexmatting.com)

# PRODUCT DATA SHEET: HERONRIB

## SIZES & WEIGHTS

All dimensions are nominal	Height (in)	Length (ft)		Widths (ft)			Weight (lbs/sq.ft)
	Tolerances +/- 0.05"	0+1.0'		+/- 1/2"			
Heronrib	13/32"	33'	2'	3'	3'3"	4'	1.10



## GENERAL

### APPEARANCES

Open grid “duckboard” design with textured surface.

### COLORS

Available in homogenous standard colors: Oxford Blue, Ocean Blue, Charcoal Gray, Mulberry Red, Forest Green, Buff and White. Mulberry Red color is not colorfast in direct sunlight. Other colors available upon request.

### DURABILITY

One piece welded construction for maintenance free life.

### WORKABILITY

Flexible construction is easy to cut and shape on site. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.

### USES

For poolside, changing rooms or where barefoot traffic is extensive, both inside or out.

## TECHNICAL DATA

### ACOUSTIC

Excellent sound absorption properties.

### CHEMICAL

Resistant to most acids, alkalines and oils. For specific chemical resistances, see [www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf](http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf)

### COMPOSITION

Flexible Polyvinyl Chloride (PVC)

### ENVIRONMENT

It has been determined under the guidelines for the State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), that no warning labels or information provision are required for Heronrib.

Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.\* in any matting products. All PCV grid products are 100% recyclable.  
\*Registration, Evaluation, Authorization and Restriction of Chemical substances

### HYGIENE

Non-porous 100% Virgin PVC - Inhibits the growth of bacteria.

Anti-bacteria Sanitized additive; Test SN195 920 – Determination of the antibacterial effect against Staphylococcus aureus ATCC 6538. Result - Nil Growth, 1mm halo, good effect.

Anti-fungal Sanitized additive; Test method ASTM G21-96; determining resistance to fungi. Result - Nil Growth after 4 weeks.

### REVERSION

Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to [www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf](http://www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf)

### SLIP RESISTANCE

ASTM F 1677 - Dry/Wet: 0.9/0.7  
DIN 51097: Classification C

### THERMAL

Functional -9°F + 140°F (slight size variation may occur at temperature extremes).

### UV LIGHT

Resistant to PVC degradation.\*  
\* Mulberry Red color is not colorfast in direct sunlight.

### WARRANTY

3 years. See [www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf](http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf)




Plastex Mattinc Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.  
Sales Tel: 256.845.7725

Web: [www.plastexmatting.com](http://www.plastexmatting.com)

# PRODUCT DATA SHEET: HERONRIB

## ANCILLARIES



3/8" x 2" x 33'  
(10mm x 50mm x 10.1m)

### 2" PVC edging strip

Supplied in rolls of 33' (10.1m) length with cold welding paste.

**Colors:** Black, Dark Gray




13/32" x 5'11"  
(10.5mm x 1.8m)

### Snap Track Low Profile

2 part snap track can be welded to join rolls end to end or side to side for large area covering. Supplied with cold welding paste.

**Color:** Dark Gray



### Connector clips - Dual purpose

For joining sections of matting together side to side or end to end. Supplied in packs of 10.

