

Cushion matting

Designed for the covering of work and storage surfaces. A bonus wherever delicate components and tools are stored or handled.

Pillomat is an all-purpose cushioned matting of tubular construction with air-filled bubble sections providing a lightweight working surface matting solution, which is ideal for a wide variety of industries - from marine compartments to general manufacturing where it is widely used on bench tops.

It is also extremely effective as a lining for shelving and compartments.



BENEFITS

- Component protection
- Good drainage and fall through
- Hygienic and easy to clean
- Easy to cut on site, contours to uneven surfaces
- Quick to install
- Fire resistant


FEATURES

- Extra smooth surface and tubular construction
- Open grid
- Non-porous PVC (impermeable to fluids)
- Made from flexible PVC
- Supplied in 33' (10m) rolls
- Certified EN 13501 - 1 : 2007- Bfl - S1


STANDARD COLOR




MAHOGANY



BEIGE



GREEN



WHITE

STANDARD SIZES

PRODUCT	HEIGHT	STANDARD ROLL OPTIONS*	
Pillomat	5/16" (8mm)	2' x 33' (0.6 x 10m)	3' x 33' (0.91 x 10m)

*Contact us for custom dimensions.




Plastex Mattinc Inc., 120 55th Street NE Fort Payne, AL 35967 U.S.A.
Sales Tel: 256.845.7725

Web: www.plastexmatting.com

PRODUCT DATA SHEET: Pillomat

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (in)	Lengths (ft)	Widths (ft)		Weight (lbs/sq.ft)
<i>Tolerances</i>	<i>+/- 0.05"</i>	<i>0+1.0'</i>	<i>+/- 1/2"</i>		
Pillomat	5/16"	33'	2'	3'	0.5



GENERAL

APPEARANCES

Open grid "duckboard" design with tubular construction.

COLORS

Available in homogeneous standard colors: Mahogany, Green, Beige, White. Mahogany color is not colorfast in direct sunlight. Other colors available on request.

DURABILITY

One piece welded construction for maintenance free life.

WORKABILITY

Flexible construction is easy to cut and shape on site.

USES

For bench tops, working surfaces and shelving.

TECHNICAL DATA

ACOUSTIC

Excellent sound absorption properties.

CHEMICAL

Resistant to most acids, alkalines and oils (for specific chemical resistances, see www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf)

COMPOSITION

Flexible Polyvinyl Chloride (PVC)

ENVIRONMENT

It has been determined under the guidelines for the State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), that no warning labels or information provision are required for Pillomat.

Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products. All PCV grid products are 100% recyclable.

* Registration, Evaluation, Authorization and Restriction of Chemical substances

HYGIENE

Non-porous 100% Virgin PVC - Inhibits the growth of bacteria.

REVERSION

Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf

THERMAL

Functional -9°F +140°F (slight size variation may occur at temperature extremes).

UV LIGHT

Resistance to PVC degradation.

WARRANTY

1 year. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf

