

Crossline Covid-19




Two-layer walkway matting with delineated safety stand zones for visitors, customers and employees



Make it easy for your customers and employees to observe social distancing measures with Crossline Covid-19, a two-layer walkway mat with color delineated stand zones.

As Covid-19 lockdown restrictions begin to ease, many businesses face the challenge of continuing or restarting operations while complying with social distancing measures. Our Crossline Covid-19 matting has delineated stand zones that make it easy to implement social distancing.

Ideal for businesses with waiting customers or workplaces with standing employees, Crossline Covid-19 is quick to install and easy to move if needed.



Features:



Diamond-cut pattern



Two-layer construction



Flexible, one-piece construction



Open grid non-porous flexible PVC



Supplied in 80' (24m) rolls



Benefits:



Certified slip resistance (ASTM I677: 1.0/0.9)



Excellent drainage through open grid



Contours to any surface



Easily cleaned & resistant to most chemicals



Quick to install and move if needed



Plastex Matting Inc.

120 55th St NE
Fort Payne, AL 35967
+1 256 845 7725

USA + UK manufactured matting products:
plastexmatting.com

Crossline Covid-19

Data sheet



Standard sizes:

Product	Crossline Covid-19
Height	13/32" (10.5mm)
Standard roll options	80' x 18" (24 x 0.45m) 80' x 2' (24 x 0.6m) 80' x 3' (24 x 0.91m)
Weight	1 lb/sq.ft (4.8 kg/m2)

Standard colors:

Black with yellow bands

More colors available upon request



Crossline Covid-19

Data sheet



Installation:

Crossline's one-piece construction means installation is simple:

- Loose lay, no fixing required
- Durable, one-piece construction
- Supplied in up to 24m rolls; place and unroll
- Easy to move if required

Cleaning:

Keeping Crossline looking good is easy:

- Simply lift or roll to clean
- Easy to clean with a high pressure hose


Technical information:

Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet .
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	Crossline Covid-19 is 100% recyclable. When manufactured in black, it's made using our post industrial recycled material. The recycled content averages at least 30%, but we strive for 100% wherever possible. We don't use any substances included in the SVHC list under REACH in any of our matting products.
Flammability	UL 94 HB Self Extinguished (material ignited but stopped burning prior to reaching the timing zone) / No Burn Rate. UL 214 self extinguished but did not reach the burn point
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by downloading this information sheet .
Slip resistance	ASTM F 1677 - Dry/Wet: 1.0/0.9
Thermal	Designed to function at temperatures from -9°F and up to +140°F. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Three years. Visit our policies page for more information about warranties

Ancillaries:

> Crossline Covid-19

PVC edging (H: 3/8", W: 2")



Supplied in rolls of 33' (10.1m) length with cold welding paste. Comes in black and dark gray. Size: 3/8" x 2" x 33' (10mm x 50mm x 10.1m)

PVC snap track (H: 13/32")



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. Supplied with cold welding paste. Comes in dark gray and black. Size: 13/32" x 8'2" (10.5mm x 2.5m)

Connector clips: dual purpose (H: 9/16")



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10