Crossgrip® 20/20



Specialized flat roof protection mat with a superior four-way drainage system, enhanced slip resistance and 10 year warranty



Introducing Crossgrip 20/20, a roof walkway system that combines all the best features of Crossgrip with an added four-way drainage system, enhanced slip resistance and an unbeatable 10-year warranty.

Crossgrip 20/20 has a redesigned base bar that boasts a superior four-way drainage system, plus a revamped top bar featuring a deeper cut for superior slip resistance (RTI) underfoot. The addition of improved UV weatherability and a 10-year warranty means Crossgrip 20/20 offers unparalleled performance, even in the most adverse conditions.

The durable, welded construction contours to the roof structure to help protect the roof surface from any potential damage, while the cross-directional top ribs ensure a firm grip underfoot.



Features:



Deep-cut pattern



Two-layer construction and channelled underbars



Flexible, one-piece construction



Loose lay, no fixing required



Supplied in 10m (33') rolls



Benefits:



Certified slip resistance (DIN 51130: R11)



Four-way drainage (DIN 51130:V10)



Contours to any surface



Stable in winds up to 60 mph/hr



Quick to install and move if needed



Plastex Matting Inc.

I 20 55th St NE Fort Payne, AL 35967 +I 256 845 7725







Crossgrip® 20/20

Data sheet





Standard sizes:

Crossgrip 20/20
I4mm (9/I6'')
I0 × 0.6m (33' × 2')
10 x 0.9 lm (33' x 3')
I0 x I.22m (33' x 4')
5.8kg/m2 (1.2 lb/sq.ft)

Standard colors:







White



Light gray



More colors available upon request

Installation:

Crossgrip 20/20's one-piece construction means installation is simple:

- Loose lay, no fixing required
- Durable, one-piece construction
- Supplied in 10m rolls; simply cut to fit on site

Cleaning:

Keeping Crossgrip 20/20 looking good is easy:

- Simply lift or roll to clean
- Easy to clean with a high pressure hose

Crossgrip® 20/20

Data sheet



Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet.
Composition	Flexible Polyvinyl Chloride (PVC)
Drainage	DIN 51130:V10
Environment	Crossgrip 20/20 is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products.
Fire	EN ISO 13501 - 1 : 2007 - Cfl - S1
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by <u>downloading this information sheet</u> .
Slip resistance	DIN 51130: R11 ASTM E303 Dry/Wet with lines along–lines across 78-90 / 63-71
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Ten years. The product will remain functional and will not degrade in such a manner as to cause leaks in the PVC roof membrane. Visit our policies page for more information about warranties.
Wind resistance	Crossgrip 20/20 remains stable in winds up to 60mph (96km/h). Tests at PRI Construction Materials Technologies LLC in Florida showed Crossgrip 20/20 when laid flat on a stable platform remained in position for wind speeds of 125mph (200 km/h).

Ancillaries:

> Crossgrip 20/20

PVC edging (H: I4mm, W: 60mm)



Supplied in rolls of 10.1m (33') length. One tube of cold welding paste recommended for every 10m of edging. Comes in black, dark grey, dark brown, holly green, Oxford blue, yellow.Size: 14mm × 60mm × 10.1m (9/16" × 2 1/2" × 33')

Connector clips: dual purpose (H: I4mm)



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10

PVC snap track (H: 14mm)



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. We recommend one tube of cold welding paste for every 10m of edging. Comes in black and dark grey. Size: 14mm × 2.5m (9/16" × 8'2")