



Heavy-duty matting with an aggressive surface designed for industrial workplaces.



Extra-aggressive matting capable of withstanding even the toughest industrial environments, Flexigrid is ideal for workplaces where spillages, debris and metal shards are an issue.

The mat's diamond-tread surface provides the highest slip resistance, while the elevated height means any hazardous matter is quickly dispersed and drained. It's also perfect for workplaces with standing employees: the two-layer construction provides comfortable cushioning to help reduce fatigue in industrial environments.



## Features:



Diamond-tread surface




Two-layer construction



Proven anti-fatigue properties



Made from flexible PVC



Comes in 5m and 10m rolls or ramped modules



## Benefits:



Certified slip resistant (DIN 51130:R11, ASTM 1677:0.6/0.5)



Excellent drainage (DIN 51130:V10)




Boosts productivity



Cut to fit on site, contours to uneven surfaces



Quick to install, easy to clean



## Plastex Matting Inc.

120 55th St NE  
Fort Payne, AL 35967  
+1 256 845 7725

USA + UK manufactured matting products:  
[plastexmatting.com](http://plastexmatting.com)

### Standard sizes:

<b>Product</b>	<b>Flexigrid</b>
<b>Height</b>	20mm (3/4")
<b>Standard roll options</b>	5 x 0.6m (16'6" x 2')
	5 x 0.91m (16'6" x 2')
	10 x 0.6m (33' x 2')
	10 x 0.91m (33' x 3')
<b>Standard module options</b>	1.8 x 0.6m (6' x 2')
	1.8 x 0.91m (6' x 3')
<b>Weight</b>	9.8kg/m <sup>2</sup> (2 lbs/sq.ft)

Surface modules are supplied with factory fitted PVC ramped edging to four sides

### Tolerances:

	Height (+/- 0.5mm)	Length (0+0.3m)	Width (+/- 1cm)
<b>Flexigrid</b>	20mm	1.8m 5m 10m	60cm 91cm

All dimensions are nominal

### Technical information:

<b>Acoustic</b>	Excellent sound absorption
<b>Chemical</b>	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this <a href="#">information sheet</a> .
<b>Composition</b>	Made from flexible Polyvinyl Chloride (PVC).
<b>Environment</b>	Flexigrid is 100% recyclable. When manufactured in black, it's made using our post industrial recycled material. The recycled content averages at least 30%, but we strive for 100% wherever possible. We don't use any substances included in the SVHC list under REACH in any of our matting products..
<b>Fire</b>	DIN 4102 Part 1- Classification B2
<b>Hygiene</b>	Made from non-porous PVC that's naturally resistant to bacteria growth.
<b>Reversion</b>	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by <a href="#">downloading this information sheet</a> .
<b>Slip resistance</b>	ASTM F 1677- Dry/Wet: 0.6/0.6 DIN 51130: R11, V10
<b>Thermal</b>	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
<b>UV light</b>	Resistant to PVC degradation
<b>Warranty</b>	Four years. Visit our <a href="#">policies page</a> for more information about warranties

### Installation:

Flexigrid's one-piece construction means installation is simple:

- Comes in 5m and 10m rolls, or choose ramped modules
- Easy to cut to fit on site
- Contours to uneven surfaces

### Cleaning:

Keeping Flexigrid looking good is easy:

- Light to handle
- Roll or lift to clean
- Easy to clean with a high pressure hose

**Colours:**




Black

More colours available upon request

**Ancillaries:**


> Flexigrid

Aluminum edging (H: 20mm)



Supplied in sections of 2m (6'6") length with fixing screws and plugs. Comes in anodized aluminum. Size: 20mm x 50mm x 2m (7/8" x 2 3/16" x 6'6")

Connector clips: dual purpose (H: 25mm)



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10