


# Floorline® Embed




Innovative embedded walkway system for liquid applied roofs



**Floorline Embed is a roof walkway system specifically designed to help keep maintenance workers safe when maintaining equipment on most liquid applied roofs.**

Floorline Embed delivers superior slip resistance and grip underfoot. The highly visible walkway has an etched surface on both the top and bottom for ease of installation and maximum securement. The flexible construction contours to and protects the roof coating, while the open grid design allows for rapid evaporation of any precipitation.

Made from non-porous PVC and compatible with various roof coatings, Floorline Embed has a five year warranty.




## Features:

Etched surface on both sides	Open-grid construction	Resistant to chemicals, acids, oils	Made from non-porous, flexible PVC	Comes in lengths up to 50m



## Benefits:

Certified slip resistant (ASTM 1677: 1.0/0.8)	Rapid evaporation of water	Easy to clean with a high pressure hose	Contours to uneven surfaces	Quick to install



## Plastic Extruders Ltd.

Russell Gardens, Wickford  
Essex, SS11 8DN  
+44 (0) 1268 571 116

UK + USA manufactured  
matting products:  
[plastexmatting.com](http://plastexmatting.com)



### Standard sizes:

<b>Product</b>	Floorline Embed
<b>Height</b>	6mm (1/4")
<b>Standard roll options</b>	0.6 x 10m (2' x 33') 0.91 x 10m (3' x 33') alternative lengths available up to max 50m (non stock availability)
<b>Weight</b>	3.70 kg/m <sup>2</sup> (0.76 lb/sq.ft)

### Tolerances:

	Height (+/- 0.5mm)	Length (0+ 0.3m)	Width (+/- 1cm)
<b>Floorline Embed</b> <i>All dimensions are nominal</i>	6mm	10m	60cm 91cm

### Technical information:


<b>Chemical</b>	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances at <a href="http://plastexmatting.com/downloads">plastexmatting.com/downloads</a>
<b>Composition</b>	Flexible Polyvinyl Chloride (PVC)
<b>Environment</b>	Floorline Embed is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products
<b>Fire</b>	DIN 4102 Part 1- Classification B2. BS 2782 Part 1, method 140A: 1992 (ISO 1210: 1992)
<b>Hygiene</b>	Made from non-porous PVC that's naturally resistant to bacteria growth. Incorporates antimicrobial and antifungal properties for continuous hygiene.
<b>Reversion</b>	Thermoplastic shrinkage can result in size reductions up to 2%, however, once embedded Floorline Embed is thermally stable.
<b>Slip resistance</b>	ASTM F 1677 - Dry/Wet: 1.0/0.8 DIN51130: R11,V10 DIN51097: Classification C
<b>Thermal</b>	Designed to function at temperatures from -23°C and up to +60°C. Once embedded Floorline Embed is thermally stable.
<b>UV light</b>	Resistant to PVC degradation. SRI values available upon request.
<b>Warranty</b>	Five years for embedded mats. Visit our policies page at <a href="http://plastexmatting.com/policies">plastexmatting.com/policies</a> for more information about warranties.

### Installation:


Floorline Embed's one-piece construction means installation is simple:

- Comes in rolls up to 50m
- Easy to cut to fit on site
- Applied directly into top coat of liquid applied roofing
- Contours to uneven surfaces
- Etched pattern on both sides for ease of installation

### Colours:



Grey



Yellow