Heronair



Slip-resistant workplace matting that's light to handle and super versatile.



Certified slip resistant with excellent drainage and anti-fatigue benefits, Heronair is perfect for light industrial workplaces and walkways where there's a risk of water underfoot.

Made from non-porous PVC with an etched pattern, Heronair is impermeable to fluids and provides excellent drainage, making it ideal for environments where spillages are likely. The hollow construction makes it light to lift and easy to move, so installation is quick and cleaning is simple. It's also a highly effective compartment liner.



Features:



Etched surface



Two layer, tubular construction



Made from nonporous PVC



Fatigue reducing and insulating



Comes in 33' (10m)



Benefits:



Certified slip resistant Excellent drainage (DIN 51130: R11, ASTM 1677: 0.6/0.6)



(DIN 51130:V10)




Chemical, oil and acid resistant



Boosts productivity



Simple to install, easy to clean



Plastex Matting Inc.

Heronair

Data sheet



Product	Heronair
Height	3/8" (10mm)
Standard roll options	33' x 2' (10 x 0.6m)
	33' x 3' (10 x 0.91m)
	33' x 4' (10 x 1.22m)
Weight	0.9lbs/sq.ft (4.5kg/m2)

Tolerances:				
	Height (+/- 0.05")	Length (0+1.0')	Width (+/- 1/2")	
Heronair	3/8''	33'	2' 3' 4'	
	•	•	•	

All dimensions are nominal

Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet.
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	Heronair is 100% recyclable. When manufactured in black, it's made using our post industrial recycled material. The recycled content averages at least 30%, but we strive for 100% wherever possible. We don't use any substances included in the SVHC list under REACH in any of our matting products
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by downloading this information sheet.
Slip resistance	ASTM F 1677 - Dry/Wet: 0.6/0.6 DIN 51130: R11,V10
Thermal	Designed to function at temperatures from -9°F and up to +140°F. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Two years. Visit our policies page for more information about warranties

Installation:

Heronair's one-piece construction means installation is simple:

- Comes in 33' rolls
- Easy to cut to fit on site
- Contours to uneven surfaces

Cleaning:

Keeping Heronair looking good is easy:

- Lightweight
- Simply roll or lift to clean
- No special cleaning tools needed
- Easy to clean with a high pressure hose

Heronair

Data sheet



Colors:



Black

More colors available upon request

Ancillaries:

> Heronair

PVC edging (H: 3/8", W: 2")



Supplied in rolls of 33' (10.1m) length with cold welding paste. Comes in black and dark gray. Size: 3/8" x 2" x 33' (10mm x 50mm x 10.1m)

Connector clips: dual purpose (H: 9/16")



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10

PVC snap track (H: 13/32")



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. Supplied with cold welding paste. Comes in dark gray and black. Size: 13/32" x 8'2" (10.5mm x 2.5m)