Heronair



Slip-resistant workplace matting that's light to handle and super versatile.



Certified slip resistant with excellent drainage and anti-fatigue benefits, Heronair is perfect for light industrial workplaces and walkways where there's a risk of water underfoot.

Made from non-porous PVC with an etched pattern, Heronair is impermeable to fluids and provides excellent drainage, making it ideal for environments where spillages are likely. The hollow construction makes it light to lift and easy to move, so installation is quick and cleaning is simple.





Plastic Extruders Ltd.

Russell Gardens, Wickford Essex, SSII 8DN +44 (0) 1268 571 116 UK + USA manufactured matting products: plastexmatting.com





Data sheet



Standard sizes:

Product	Heronair
Height	10mm (3/8'')
Standard roll options	10 x 0.5m (33' x 1'8'')
	10 x 0.75m (33' x 2'5'')
	10 x lm (33' x 3'3'')
Weight	4.5kg/m2 (0.6lbs/sq.ft)

Tolerances:

T leight	: (+/- 0.5mm)	Length (0+0.3m)	Width (+/- 1cm)
Heronair 10mm		10m	50cm 75cm 100cm

All dimensions are nominal

Technical information:

Acoustic	Excellent sound absorption		
Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet.		
Composition	Flexible Polyvinyl Chloride (PVC)		
Environment	Heronair is 100% recyclable. When manufactured in black, it's made using our post industrial recycled material. The recycled content averages at least 30%, but we strive for 100% wherever possible. We dor use any substances included in the SVHC list under REACH in any of our matting products		
Fire	DIN 4102 Part 1 – Classification B2		
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.		
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by <u>downloading this information sheet</u>		
Slip resistance	ASTM F I 677- Dry/Wet: 0.6/0.6 DIN 51130: R11,V10		
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur a temperature extremes.		
UV light	Resistant to PVC degradation		
Warranty	Two years. Visit our policies page for more information about warranties		

Installation:

Heronair's one-piece construction means installation is simple:

- Comes in 10m rolls
- Easy to cut to fit on site
- Contours to uneven surfaces

Cleaning:

Keeping Heronair looking good is easy:

- Lightweight
- Simply roll or lift to clean
- No special cleaning tools needed
- Easy to clean with a high pressure hose



Data sheet



