



Cushioned animal cage matting that's hygienic, comfortable and easy to clean.



Create a warm and inviting environment for animals to lie and stand on with HVD, cushioned matting that provides both cleanliness and comfort.

Made from non-toxic, flexible PVC with a smooth upper surface, it ensures a comfortable and hygienic environment for all types of animals. The two-layer construction elevates the animal off the surface and the open grid provides a high level of drainage, making it ideal for veterinary clinics, kennels, research facilities and zoos.



Features:



Extra smooth surface



Two layer construction



Made from non-toxic, inert PVC



Flexible construction



Supplied in 10m (33') rolls



Benefits:



Creates a comfortable environment



High level of drainage



Hygenic and easy to clean



Easy to cut to fit on site



Quick to install





Data sheet



Standard sizes:		
HVD		
13.5mm (17/32'')		
10 × 0.6m (33' × 2')		
10 × 0.9 lm (33' × 3')		
10 x 1.22m (33' x 4')		
6.9kg/m2 (1.4lb/sq.ft)		

Tolerances:			
	Height (+/- 0.5mm)	Length (0+0.3m)	Width (+/- Icm)
HVD	13.5 mm	10 m	60cm 91 cm 122 cm

Acoustic	Excellent sound absorption properties		
Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this <u>information sheet</u> .		
Composition	Flexible Polyvinyl Chloride (PVC)		
Environment	HVD is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products.		
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.		
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by downloading this information shee		
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.		
UV light	Resistant to PVC degradation		
Warranty	Two years. Visit our policies page for more information about warranties		

Installation:

HVD's one-piece construction means installation is simple:

- Supplied in 10m rolls
- Easy to cut to fit on site
- Contours to uneven surfaces

Cleaning:

Keeping HVD looking good is easy:

- Light to handle
- Simply roll or lift to clean
- No special cleaning tools needed



Data sheet



Colours:





Black

Blue

More colours available upon request

Ancillaries:

> HVD

PVC edging (H: I4mm, W: 60mm)



Supplied in rolls of 10.1m (33') length. One tube of cold welding paste recommended for every 10m of edging. Comes in black, dark grey, dark brown, holly green, Oxford blue, yellow. Size: 14mm × 60mm × 10.1m (9/16" × 2 1/2" × 33").

Aluminum edging (H: 15mm)



Supplied in sections of 2m (6'6") length with fixing screws and plugs. Comes in anodized aluminum and powder coated yellow. Size: 15mm × 45mm × 2m (5/8" × 1 13/16" × 6'6")

Large floor hooks (H: 14mm)



For securing sections of matting to the floor. Supplied in packs of 10 with screws and plugs

Connector clips: dual purpose (H: I4mm)



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10

PVC edging (H: 14mm, W: 100mm)



Supplied in rolls of 10.1m (33') length. One tube of cold welding paste recommended for every 10m of edging.

Comes in black, dark grey and yellow. Size: 14mm × 100mm × 10.1m (9/16" × 3 3/4" × 33')

PVC snap track (H: 14mm)



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. We recommend one tube of cold welding paste for every 10m of edging. Comes in black and dark grey. Size: 14mm × 2.5m (9/16" × 8'2")

Small floor hook (H: 14mm)



For securing sections of matting to the floor. Supplied in packs of 20 with screws and plugs