



plastex

# Cushioned animal cage matting that's hygienic, comfortable and easy to clean.



Create a warm and inviting environment for animals to lie and stand on with HVD, cushioned matting that provides both cleanliness and comfort.

Made from non-toxic, flexible PVC with a smooth upper surface, it ensures a comfortable and hygienic environment for all types of animals. The two-layer construction elevates the animal off the surface, while the open grid provides a high level of drainage, making it ideal for veterinary clinics, kennels, research facilities and zoos.



# Features:



Extra smooth surface



Two layer construction



Made from non-toxic, inert PVC



Flexible construction



Supplied in 33' (10m) rolls



# **Benefits:**



Creates a comfortable environment



High level of drainage



Hygenic and easy to clean



Easy to cut to fit on site



Quick to install



#### Plastex Matting Inc.



# Data sheet



Product	HVD
Height	17/32" (13.5mm)
Standard roll options	33' × 2' (10 × 0.6m)
	33' × 3' (10 × 0.91m)
	33' x 4' (10 x 1.22m)
Weight	1.4 lb/sq.ft (6.9 kg/m2)

	Height (+/- 0.05")	Length (0+ 1.0')	Width (+/- 1/2")
HVD	17/32''	33'	2' 3' 4'

Acoustic	Excellent sound absorption properties
Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet.
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	HVD is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products.
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by <u>downloading this information sheet</u> .
Thermal	Designed to function at temperatures from -9°F and up to +140°F. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Two years. Visit our policies page for more information about warranties

# Installation:

HVD's one-piece construction means installation is simple:

- Supplied in 33' rolls
- Easy to cut to fit on site
- Contours to uneven surfaces

# Cleaning:

Keeping HVD looking good is easy:

- Light to handle
- Simply roll or lift to clean
- No special cleaning tools needed



# Data sheet



#### **Colors:**







More colors available upon request

#### **Ancillaries:**

> HVD

#### PVC edging (H: 9/16, W: 2 1/2'')



Supplied in rolls of 33' (10.1m) length with cold welding paste. Comes in black, dark gray, dark brown, holly green, Oxford blue, yellow. Size: 9/16" x 2 1/2" x 33' (14mm x 60mm x 10.1m)

# PVC edging (H: 9/16, W: 3 3/4")



Supplied in rolls of 33' (10.1m) length with cold welding paste. Comes in black, dark gray and yellow. Size: 9/16" × 3 3/4" × 33' (14mm × 100mm × 10.1m)

#### Aluminum edging (H: 5/8'')



Supplied in sections of 6'6" (2m) length with fixing screws and plugs. Comes in anodized aluminum and powder coated yellow. Size: 5/8" x | 13 /16" x 6'6" (15mm x 45mm x 2m)

#### PVC snap track (H: 9/16")



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. Supplied with cold welding paste. Comes in dark gray. Size: 9/16" x 8'2" (14mm x 2.5m)

# Large floor hooks (H: 9/16")



For securing sections of matting to the floor: Supplied in packs of 10 with screws and plugs

# Small floor hook (H: 9/16")



For securing sections of matting to the floor. Supplied in packs of 20 with screws and plugs

# Connector clips: dual purpose (H: 9/16")



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10